

Cleaner

Cleaner for sanded wood

Cleaner is used after sanding and vacuuming the wood and guarantees a thorough cleaning of the surface before it is treated with Oil Plus 2C. This product removes even the smallest dust particles.

The Cleaner can also be used to clean the materials used after oiling, such as brushes, spatulas, etc.



PRODUCT INFORMATION

› Specific characteristics

Why **use a small amount** of Cleaner?

- The revolutionary technology of Oil Plus 2C uses molecular binding to ensure that the oil binds with the wood fibres within 15 seconds. If there is dust on the surface, the oil will bond with the dust. As a result, when spreading the oil with the white pad, a microscopic paste will form on the surface. The oil will have bonded with the dust instead of with the wood fibres.
- The cloth should only be slightly damped with Cleaner. In that way the dust will be collected electrostatically.

› Technical characteristics

- Physical state at 20 °C: liquid
- Colour: clear
- Final boiling point [°C]: 213 °C
- Density [kg/m³]: 0,7 (15 °C)
- Viscosity: 1,67 mm²/s (25°C)
- Solubility in water: < 0,10 %
- Flash point [°C]: > 62 °C

› Packaging



› Storage

The product can be stored up to 36 months in dry conditions and in its original packaging. Keep away from frost.

APPLICATION INFORMATION

› Instructions

STEP 1. Sand and vacuum the surface in the appropriate manner.

STEP 2. Clean the surface with Cleaner.

STEP 3. Allow the wood to dry until it regains its original aspect.

- **Drying time:** 15 minutes to 1 hour, depending on the degree of product that has been used to wet the surface.

› Consumption

± 75-100 m²/L

** These usages are merely indicative. Results depend on wood type and method of preparation. It is always recommended to make a sample in order to calculate the exact usage.*

Check the packaging and the safety data sheet for more details.

For our complete assortment of products for the protection and colouring of interior and exterior wood, please visit www.rubimonocoat.com

LIABILITY: It is the user's responsibility to establish, through his own tests, whether the product is suitable for the chosen application. In no case can Muylle Facon NV be held liable for any consequential damage. The information above may be subject to changes, which will be published in the updated versions of the technical data sheet. We cannot be held liable for poor results due to causes that are not related to the quality of the product. This technical information has been drawn up based on the currently available information and knowledge. The most recent technical data sheets can be requested or are available on the website.

Date of TDS: 17/09/2025. Check the safety information before using the product.



Rubio[®]
MONOCOAT
MUYLLE  FACON

Muylle Facon NV
Ambachtenstraat 58
8870 Izegem (BELGIUM)

Phone +32 (0) 51 30 80 54
Fax +32 (0) 51 30 99 78
info@muyllefacon.be

www.rubimonocoat.com